

Commerce Management System 5

Marketplace 5.0

uPay Technical Guide

January 2010

This document contains confidential information and may not be duplicated or disclosed to third parties, in whole or in part, for any purpose, without the prior express written consent of TouchNet Information Systems, Inc.

Information represented in this document is subject to development and change without notice.

Copyright 2010 TouchNet Information Systems, Inc.

All rights reserved.

TouchNet® and the TouchNet logo are trademarks of TouchNet Information Systems, Inc.

Other trademarks within this document are the property of their respective owners. Other product or company names may be trademarks of their respective owners.

Last updated for Marketplace release 5.0.4

Document release date: January 14, 2010

Contents

1.0 Passing Parameters to Your uPay Site	1
2.0 Using a Posting URL	9
3.0 About Recurring Payment Parameters	15

1.0 Passing Parameters to Your uPay Site

For uPay to integrate with a campus web application, the campus web application must be able to pass parameters that describe the transaction. At a minimum, the campus web application must pass a uPay site ID that identifies which uPay site will handle the transaction. In addition, in order for a transaction to be identified and tracked, the campus web application must pass a transaction ID (called EXT_TRANS_ID by uPay).

Some parameters can be used to automatically populate fields on your uPay site. For example, the customer's billing address can be passed to uPay so that the customer isn't required to re-enter this information. Likewise, a dollar amount can be passed directly to uPay.

You do not need to tell Marketplace which parameters you will be passing. You only need pass the parameters when directing a customer to your uPay site. uPay will accept any parameters that you pass and in turn pass the parameters back to your campus web application after the transaction is processed (provided you use the posting URL option, as described in Section 2.0 , "Using a Posting URL" on page 9).



uPay Parameter Details

In order for uPay to take action on passed parameters (such as pre-populating the billing address fields or the dollar amount field), the parameters must be named as described below.

If the campus web application passes recurring payment data—RECURRING_USER_CAN_CHANGE, RECURRING_FREQUENCY, RECURRING_START_DATE, and RECURRING_NUMBER_OF_PAYMENTS or RECURRING_END_DATE—to the uPay site, uPay will then take that data and calculate the payment schedule.

Note: To receive back the payment parameters after the payment is completed in uPay, a posting URL must be used, as described in "Using a Posting URL" on page 9. If recurring payments are used, this payment information becomes critical for monitoring the payment process. For example, if recurring payment parameters are sent to the Posting URL, the campus web application will have a record of when the last payment is due.

The following list describes all the parameters that uPay can use. uPay takes actions on these following parameters.

Parameters that uPay takes action upon receiving:

Parameters	Description	Field Length	Data Type
UPAY_SITE_ID	Required. This is a numerical value unique to each uPay site. The value is displayed in the Form Parameters page for the uPay site.	unlimited	numeric
BILL_NAME	Used to pass the billing name.	50	alphanumeric
BILL_EMAIL_ADDRESS	Used to pass the billing e-mail address.	50	alphanumeric
BILL_STREET1	Used to pass the billing street address 1.	35	alphanumeric
BILL_STREET2	Used to pass the billing street address 2.	35	alphanumeric
BILL_CITY	Used to pass the billing city.	35	alphanumeric
BILL_STATE	Used to pass the billing state. The billing state should be passed as the two-character state abbreviation. For foreign addresses, "--" can be passed to uPay in order to select "Not applicable" for the state field.	2	alphanumeric
BILL_POSTAL_CODE	Used to pass the billing postal code. To accommodate foreign addresses, uPay will accept up to 30 characters in the postal code parameter.	30	alphanumeric

Parameters	Description	Field Length	Data Type
BILL_COUNTRY	Used to pass the two-letter country code for the billing country. (We recommend using the two-letter English language country codes approved by the International Organization for Standardization codes. This list can be found at www.iso.org/iso/country_codes.htm .)	2	alphanumeric
EXT_TRANS_ID	<p>Optional. This ID is generated by the campus web application. It serves as a cross-reference between the web application and Marketplace. If this parameter is passed to uPay, it will be stored in the Marketplace database along with the payment information.</p> <p>If you are posting payment results to an external URL, this parameter will be sent along with the posted data.</p> <p>Using EXT_TRANS_ID as the field name of the transaction ID that you pass to uPay allows you to use Marketplace's uPay Payment Search functionality to search for payments with a specified EXT_TRANS_ID value. In addition, you will be able to view the EXT_TRANS_ID values on Marketplace's Posting Status Report.</p>	250	alphanumeric
EXT_TRANS_ID_LABEL	Optional. This field can contain a description of the EXT_TRANS_ID value. If this parameter is used, this description appears on the receipt that the customer sees at the end of the uPay payment process.	unlimited	alphanumeric
AMT	Optional. If used, this parameter fills in the payment amount field in uPay. To use this parameter, you must configure your uPay site to allow the amount to be passed in. This option is in the Payment Method Settings page for your uPay site. By default, T-Link expects the payment amount to be passed with the AMT parameter from the web application. If a payment amount is not passed, the uPay site's default payment amount will be displayed to the customer. For more about payment settings, see "Payment Settings". (Maximum value: \$99,999.99.)	8 (including 2 characters after the decimal)	numeric

Parameters	Description	Field Length	Data Type
SSV	<p>This parameter can be used only used if you accept ACH payments. This is the Shared Secret Value that the user enters on the ACH agreement page when paying by checking or savings account.</p> <p>A shared secret value is an alphanumeric value that the user knows, for example, their birth year or their mother's maiden name. While the shared secret value is not required by uPay, it is a requirement of the NACHA rules for web-based ACH payments. Having users enter a shared secret value increases security of payments through electronic bank accounts.</p>	unlimited	alphanumeric
SSV_PROMPT	<p>This parameter can only be used if you accept ACH payments. The SSV_PROMPT is used when the user pays by checking or savings account. If passed, it overrides your setting for the Shared Secret Value prompt. This is the prompt shown to users so they know what to enter for the Shared Secret value. If the prompt value is not passed, uPay uses the prompt you define in the Payment Method Settings page.</p>	unlimited	alphanumeric
VALIDATION_KEY	<p>This option requires you to use the posting key (as described in "Miscellaneous: Links, URLs, and E-mail" on page 138). For security, it is highly recommended that you use the posting key when you are allowing an amount to be passed to the uPay site. The posting key is used to assure that the amount being passed in has not been altered prior to form submission.</p>	unlimited	alphanumeric
RECURRING_USER_CAN_CHANGE	<p>Optional. In order to establish a recurring payment plan, this parameter MUST be passed.</p> <p>This parameter determines whether the customer can change the recurring payment values that are passed by the campus web application. Accepted values: True or False.</p> <p>Note: If RECURRING_USER_CAN_CHANGE = false, uPay must receive RECURRING_START_DATE, RECURRING_FREQUENCY and RECURRING_END_DATE or RECURRING_NUMBER_OF_PAYMENTS. If uPay does not receive these values, uPay will display an error message to the customer.</p>	unlimited	alphanumeric

Parameters	Description	Field Length	Data Type
RECURRING_CAN_CHANGE_END_DATE_TO_CC_EXP_DATE	<p>If recurring payment parameters are being sent to the uPay site, this parameter determines what happens if the customer enters a credit card expiration date that will occur <i>before</i> the projected end date of the payment plan. Accepted values: Yes or No.</p> <p>If RECURRING_EXP_DATE_CHANGE = Yes and the customer enters a credit card expiration date that will occur before the projected end date of the payment plan, uPay will automatically change the payment plan's end date so it comes before the credit card expiration date. If RECURRING_EXP_DATE_CHANGE = No and the customer enters a credit card expiration date that will occur before the projected end date of the payment plan, uPay will prompt the customer to use a different credit card.</p> <p>Example: The customer uses the campus web application to make a monthly donation of \$100. In the campus web application, the customer enters the following information for the recurring payment plan: start date - 10/26/2008, frequency - monthly, and end date - 06/26/10. This information is passed to uPay by the campus web application, at which point the customer enters their credit card information. The customer enters a credit card expiration date of 04/10—which predates the payment plan's end date. Because the campus web application sent RECURRING_EXP_DATE_CHANGE = Yes, uPay automatically changes the date of the last payment to 4/26/10. The monthly donation remains unchanged at \$100.</p> <p>Note: RECURRING_CAN_CHANGE_END_DATE_TO_CC_EXP_DATE = Yes should only be used in situations in which it is acceptable that the total dollar amount of payments made over the course of a payment plan be reduced by the elimination of one or more payments. RECURRING_CAN_CHANGE_END_DATE_TO_CC_EXP_DATE = Yes might work well with donations, in which the alternative of the customer canceling the entire payment plan would be less desirable than the elimination of one or more payments within a plan. In contrast, the elimination of payments for a product that is actually delivered to the customer, such as a parking pass or a football season ticket, would most likely be considered unacceptable.</p>	unlimited	alphanumeric

Parameters	Description	Field Length	Data Type
RECURRING_START_DATE	If the uPay site accepts recurring payments, this parameter determines the start date for the recurring payment plan. The customer must enter today's date or a later date (i.e., the customer cannot enter a past date). Required date format: mm/dd/yyyy.	10	alphanumeric
RECURRING_END_DATE	If the uPay site accepts recurring payments, this parameter determines the end date for the recurring payment plan. Required date format: mm/dd/yyyy.	10	alphanumeric
RECURRING_FREQUENCY	If the uPay site accepts recurring payments, this parameter sets the frequency of the payment plan. Accepted values: 1 (Monthly), 2 (Bi-Monthly), 4 (Weekly), 5 (Quarterly), 6 (Semi-Annually), and 7 (Annually). Note: For RECURRING_FREQUENCY, be sure to use the accepted numerical values. For example, to set up a weekly recurring payment plan, send RECURRING_FREQUENCY = 4; Do not send RECURRING_FREQUENCY = Weekly.	unlimited	numeric
RECURRING_NUMBER_OF_PAYMENTS	If the uPay site accepts recurring payments, this parameter determines the number of payments in the payment plan. Note: If both RECURRING_NUMBER_OF_PAYMENTS and RECURRING_END_DATE are passed to uPay, uPay will use RECURRING_NUMBER_OF_PAYMENTS to calculate the payment schedule.	unlimited	numeric
SUCCESS_LINK	Optional. When you establish a uPay site, you enter a URL for the success link that appears on the receipt page the customer sees after successfully making a uPay payment. Instead of providing the same URL for all customers, you can customize the success link URL. For example, for customers identified as students, you might return them to a student portal web site, while parents might be returned to a portal designed for the parents of students.	unlimited	alphanumeric

Parameters	Description	Field Length	Data Type
SUCCESS_LINK_TEXT	Optional. This text appears as a hyperlink on the receipt page that customers see after successfully making a payment with uPay. While the SUCCESS_LINK parameter provides the URL for the hyperlink, the SUCCESS_LINK_TEXT parameter provides the text for the hyperlink.	unlimited	alphanumeric
ERROR_LINK	Optional. When you establish a uPay site, you enter a URL for the error link that appears on the error page that the customer sees when a system error occurs while attempting to make payment. Instead of providing the same URL for all customers, you can customize the link that appears when an error is encountered.	unlimited	alphanumeric
ERROR_LINK_TEXT	Optional. This text appears as a hyperlink on the error page that customers see after a system error occurs while attempting to make a payment with uPay. While the ERROR_LINK parameter provides the URL for the hyperlink, the ERROR_LINK_TEXT parameter provides the text for the hyperlink.	unlimited	alphanumeric
CANCEL_LINK	Optional. When you establish a uPay site, you enter a URL for the cancel link that appears throughout your uPay site. Instead of providing the same URL for all customers, you can customize the link that appears when an error is encountered.	unlimited	alphanumeric
CANCEL_LINK_TEXT	Optional. This text appears when a uPay customer places their cursor over the Cancel button. (Only works with Microsoft Internet Explorer.) In the HTML for the uPay site, this text is added as the ALT attribute of the Cancel button (which appears in the HTML as an IMG tag).	unlimited	alphanumeric
CREDIT_ACCT_CODE	(Only displayed for Banner users.) This parameter contains the credit accounting code.	unlimited	alphanumeric
DEBIT_ACCT_CODE	(Only displayed for Banner users.) This parameter contains the debit accounting code.	unlimited	alphanumeric

2.0 Using a Posting URL

After a transaction is processed, uPay can pass parameters describing the transaction back a campus web application. This information can include parameters that were initially passed to uPay from a web application, such as a transaction ID (as described in ["Passing Parameters to Your uPay Site" on page 1](#)). In addition, these parameters can include information about the status of the transaction (as determined by Payment Gateway). When this information is posted, the status of the transaction can be updated on the campus system.

Note: Campus web applications do not necessarily need to pass a transaction ID to uPay; however, without a transaction ID the campus organization will have no way to match payment information with customer information. In effect, the campus organization would be accepting payments blindly, which might be acceptable for donations; however, even with donations, the campus organization would almost certainly want to track information about the donor beyond the payment fields required for monetary transactions in uPay.



Posting URL Parameters

Once a uPay site has been configured to use a posting URL, transaction parameters will be passed by uPay to the posting URL. The customer's browser is not navigated to the posting URL, but the parameters are posted to it. The web application targeted by the posting URL must be able to process these parameters. It is your responsibility to contact the administrator of the campus web application and provide that person with information about the posting-URL parameters.

Important! Technical details on configuring a campus web application to accept the parameters passed to a posting URL are outside the scope of this document.

The following parameters are posted along with any other parameters that the web application initially passed to uPay:

Parameters for credit card transactions and ACH transactions:

Parameters	Description	Field Length	Data Type
posting_key	A security value specified when the uPay site was built.	30	alphanumeric
tpg_trans_id	A reference number assigned by Payment Gateway.	unlimited	alphanumeric
pmt_status	Status of the transaction as reported by Payment Gateway. Either "success" or "cancelled".	unlimited	alphanumeric
pmt_amt	Amount of the transaction processed by Payment Gateway. (Maximum value: \$99,999.99.)	8 (including 2 characters after the decimal point)	numeric
pmt_date	Date the transaction was processed by Payment Gateway. (Format: mm/dd/yyyy.)	unlimited	alphanumeric
name_on_acct	Name on credit card account or bank account.	50	alphanumeric
acct_addr	The address entered by the customer in uPay. This parameter is passed only if the uPay site has been set up to require address verification data.	35	alphanumeric
acct_addr2	The second address line entered by the customer in uPay. This parameter is passed only if the uPay site has been set up to require address verification data.	35	alphanumeric
acct_city	The city entered by the customer in uPay. This parameter is passed only if the uPay site has been set up to require address verification data.	35	alphanumeric

Parameters	Description	Field Length	Data Type
acct_state	The state entered by the customer in uPay. This parameter is passed only if the uPay site has been set up to require address verification data.	2	alphanumeric
acct_zip	The zip code entered by the customer in uPay. This parameter is passed only if the uPay site has been set up to require address verification data.	30	alphanumeric
acct_email_address	The customer can be required to enter an e-mail address or this field can be optional.	50	alphanumeric
acct_phone_day	This phone field is an optional entry field.	20	alphanumeric
acct_phone_night	This phone field is an optional entry field.	20	alphanumeric
acct_phone_mobile	This phone field is an optional entry field.	20	alphanumeric
EXT_TRANS_ID	An ID generated/assigned by your campus web application. This value is posted only if it was initially passed to uPay from the campus web application.	250	alphanumeric
UPAY_SITE_ID	A unique ID that identifies the uPay site. Assigned by Marketplace when the uPay site was created.	unlimited	numeric
sys_tracking_id	An internal Marketplace identifier (also known as the order ID) that is displayed to the customer on the uPay receipt page.	unlimited	numeric
recurring_payment_type	This value is specified if the payment is a recurring payment. Two values are possible: "setup" (for the initial setup of a recurring payment plan) and "payment" (for one payment in a recurring payment plan).	unlimited	alphanumeric
recurring_setup_number_of_payments	This value is specified for recurring payment plans and indicates the total number of payments in the plan.	unlimited	numeric
recurring_setup_start_date	This value is specified for recurring payment plans and indicates the date of the first payment in the plan. (Format: mm/dd/yyyy.)	10	alphanumeric

Parameters	Description	Field Length	Data Type
recurring_setup_end_date	This value is specified for recurring payment plans and indicates the date when the payment plan ends. If this date does not coincide with a scheduled payment date (as determined by the selected frequency and start date), the final payment will be the last regularly scheduled payment date before the "recurring_setup_end_date". (Format: mm/dd/yyyy.)	10	alphanumeric
recurring_setup_frequency	This numerical value is specified for recurring payment plans and indicates the frequency of payments: 4 = weekly, 1 = monthly, 2 = bi-monthly, 5 = quarterly, 6 = semi-annually, and 7 = annually.	unlimited	numeric

Additional parameters for credit card transactions:

Parameters	Description	Field Length	Data Type
card_type	Type of credit card: MasterCard, Visa, AmEx, Discover, etc.	unlimited	alphanumeric

Additional parameters for ACH transactions:

Parameters	Description	Field Length	Data Type
bank_name	These values are obtained from Payment Gateway based on the routing number entered	unlimited	alphanumeric
bank_addr1	These values are obtained from Payment Gateway based on the routing number entered	unlimited	alphanumeric
bank_addr2	These values are obtained from Payment Gateway based on the routing number entered	unlimited	alphanumeric
bank_routing_num	These values are obtained from Payment Gateway based on the routing number entered	unlimited	alphanumeric

Parameters for cancellations:

Parameters	Description	Field Length	Data Type
posting_key	A security value specified when the uPay site was built.	unlimited	alphanumeric
pmt_status	This value is always "cancelled" for cancellations.	unlimited	alphanumeric

Parameters	Description	Field Length	Data Type
EXT_TRANS_ID	A unique ID generated/assigned by your campus web application. This value is posted only if it was initially passed to uPay from the campus web application.	250	alphanumeric
UPAY_SITE_ID	A unique ID that identifies the uPay site. Assigned when the uPay site was created.	unlimited	numeric

3.0 About Recurring Payment Parameters

For recurring payment plans, the following parameters are passed when the payment plan is established and for each payment:

- sys_tracking_id
- posting_key
- name_on_acct
- acct_addr
- acct_addr2
- acct_city
- acct_state
- acct_zip
- acct_email_address
- acct_phone_day
- acct_phone_night
- acct_phone_mobile
- UPAY_SITE_ID
- card_type
- pmt_amt
- recurring_payment_type
- recurring_setup_number_of_payments
- recurring_setup_start_date
- recurring_setup_end_date
- recurring_setup_frequency

Note: During plan setup, the total amount of all payments in the plan is passed to the posting URL as the pmt_amt parameter. This is the same parameter used for each recurring payment in the plan. The campus web application must be able to use the value passed to the posting URL in the recurring_payment_type parameter (either "setup" or "payment") to determine if pmt_amt represents a total for a plan setup or the amount for an individual recurring payment.

And the following additional parameters are passed for each payment in a recurring payment plan (not when the plan is established):

- pmt_status
- pmt_date
- tpg_trans_id

